

STANLEY®



Instant Adhesive

An adhesive set which consists of high viscosity cyanoacrylate adhesive and activator.



www.STANLEYCHEM.com
contact@stanleychem.com

Stanley®, the Stanley® logo, the thick and thin horizontal line field, and the engineering plan packaging design are trademarks of Stanley Black & Decker, Inc. or an affiliate thereof, used under license.

Fast, Easy and Practical

PROPERTIES

- High bonding strength.
- Suitable for use on vertical surfaces as it will not drip or slump.
- It is particularly suited to bonding difficult substrates which have a porous or uneven nature since it increases bonding strength by preventing the adhesive to be absorbed by the surface.

APPLICATION AREAS

- It is suitable for the bonding of a very wide range of materials, including acidic surfaces and some porous ones, where rapid bonding times are required.
- Suitable for MDF, wood, chip wood, rubber, most plastics, leather and other common substrates.
- Especially suitable for the applications where cure speed needs to be accelerated.


Can be used on almost any material, including wood, stone, marble, ceramic, leather, PVC, metal, etc..



WOOD



STONE



ALUMINUM



CERAMIC

HOW TO USE?

STEP 1



Apply the activator and wait for 10 seconds

STEP 2



Apply the gel

STEP 3



Press for a couple of seconds

* The results were obtained by providing optimum environmental conditions.