

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

NUCLEUS INCORPORATED
 13901 WILLARD RD, CHANTILLY, VA 20151
 +1 571 445 5665

1.4. Emergency telephone number

For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident
 Call CHEMTREC Day or Night
[1-800-424-9300](tel:1-800-424-9300)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable aerosols, Category 1	H222 Extremely flammable aerosol.
Skin corrosion/irritation, Category 2	H315 Causes skin irritation.
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336 May cause drowsiness or dizziness.
Specific target organ toxicity — Repeated exposure, Category 2	H373 May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411 Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : H222 - Extremely flammable aerosol.
 H315 - Causes skin irritation.
 H336 - May cause drowsiness or dizziness.
 H373 - May cause damage to organs through prolonged or repeated exposure.
 H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source.
 P251 - Do not pierce or burn, even after use.
 P260 - Do not breathe dust, fume, gas, mist, spray, vapours.
 P271 - Use only outdoors or in a well-ventilated area.
 P273 - Avoid release to the environment
 P280 - Wear protective clothing, eye protection, face protection, protective gloves.
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
n-hexane	(CAS-No.) 110-54-3	50 – 70	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).]	(CAS-No.) 68476-85-7	30 – 40	Flam. Gas 1, H220
N,N-dimethyl-p-toluidine	(CAS-No.) 99-97-8	0.1 – 1	Flam. Liq. 4, H227 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Inhalation), H331 STOT RE 2, H373

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

705 FAST ADHESIVE ACTIVATOR	
No additional information available	
n-hexane (110-54-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Hexane
ACGIH TWA (ppm)	50 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; peripheral neuropathy; eye irr. Notations: Skin; BEI
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
Local name	n-HEXANE
Biological Exposure Indices (BEI)	0.5 mg/l Parameter: 2,5-Hexanedione (without hydrolysis) - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	n-Hexane
OSHA PEL (TWA) (mg/m³)	1800 mg/m³
OSHA PEL (TWA) (ppm)	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] (68476-85-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	L.P.G (Liquefied petroleum gas)
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2020

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

USA - OSHA - Occupational Exposure Limits	
Local name	L.P.G. (Liquified petroleum gas)
OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA PEL (TWA) (ppm)	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
N,N-dimethyl-p-toluidine (99-97-8)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
 Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves. EN 374

Eye protection:

Safety glasses. EN 166

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. EN 14387

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquid under pressure.
Colour	: Colourless
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 64 – 72 °C
Flash point	: < 60 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

Density	: 0.78 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content : 89 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

N,N-dimethyl-p-toluidine (99-97-8)	
LD50 oral rat	1650 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	1.4 mg/l air Animal: rat, Guideline: other:
ATE US (oral)	139 mg/kg bodyweight
ATE US (gases)	700 ppmv/4h
ATE US (vapours)	3 mg/l/4h
ATE US (dust,mist)	0.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

N,N-dimethyl-p-toluidine (99-97-8)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

n-hexane (110-54-3)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

n-hexane (110-54-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

N,N-dimethyl-p-toluidine (99-97-8)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

N,N-dimethyl-p-toluidine (99-97-8)	
LC50 fish 1	46 mg/l Test organisms (species): Pimephales promelas

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	:	UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
UN-No.(DOT)	:	UN1950
Proper Shipping Name (DOT)	:	Aerosols flammable, (each not exceeding 1 L capacity)
Class (DOT)	:	2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	:	2.1 - Flammable gas



Dangerous for the environment	:	Yes
Marine pollutant	:	Yes



DOT Packaging Non Bulk (49 CFR 173.xxx)	:	None
DOT Packaging Bulk (49 CFR 173.xxx)	:	None
DOT Special Provisions (49 CFR 172.102)	:	N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols
DOT Packaging Exceptions (49 CFR 173.xxx)	:	306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	150 kg
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
DOT Vessel Stowage Other	:	25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials
Emergency Response Guide (ERG) Number	:	126
Other information	:	No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG)	:	1950
Proper Shipping Name (IMDG)	:	AEROSOLS
Class (IMDG)	:	2 - Gases
MFAG-No	:	126

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

Air transport

UN-No. (IATA)	:	1950
Proper Shipping Name (IATA)	:	Aerosols, flammable
Class (IATA)	:	2
UN-No. (IATA)	:	1950

SECTION 15: Regulatory information

15.1. US Federal regulations

n-hexane (110-54-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] (68476-85-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
N,N-dimethyl-p-toluidine (99-97-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

n-hexane (110-54-3)	
Listed on the Canadian DSL (Domestic Substances List)	
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).] (68476-85-7)	
Listed on the Canadian DSL (Domestic Substances List)	
N,N-dimethyl-p-toluidine (99-97-8)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

National regulations

N,N-dimethyl-p-toluidine (99-97-8)
Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

n-hexane (110-54-3)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	No	No	Yes		28000 µg/day (oral); 20,000 µg/day (inhalation)

STANLEY INSTANT STONE&MARBLE GLUE ACTIVATOR

Issue date: 17.07.2023 Version: 0.0

N,N-dimethyl-p-toluidine (99-97-8)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
n-hexane(110-54-3)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately- 40°C to 80°C (- 40°F to 176°F).](68476-85-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-statements:

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H227	Combustible liquid
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

SDS US STANLEY

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable