

1. Identification

1.1. Product identifier

Trade name

Stanley F 993 Foam Sealant Pest Block

Product form

Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

No information available

1.3. Details of the supplier of the safety data sheet

NUCLEUS INCORPORATED**13901 WILLARD RD, CHANTILLY, VA 20151****+1 703 988 7773**

1.4. Emergency telephone number

For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

1-800-424-9300

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200).

The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Aerosol, category 1

Carcinogenicity, category 2

Acute toxicity, category 4

Specific target organ toxicity - repeated exposure, category 2

Eye irritation, category 2

Skin irritation, category 2

Specific target organ toxicity - single exposure, category 3

Respiratory sensitization, category 1

Skin sensitization, category 1

Hazardous to the aquatic environment, chronic toxicity, category 2

Extremely flammable aerosol.

Suspected of causing cancer.

Harmful if inhaled.

May cause damage to organs through prolonged or repeated exposure.

Causes serious eye irritation.

Causes skin irritation.

May cause respiratory irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

Hazard pictograms:



Signal words:

Danger



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

Hazard statements:

H222	Extremely flammable aerosol.
H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust / fume / gas / mist / vapours / spray.
P202	Do not handle until all safety precautions have been read and understood.
P201	Obtain special instructions before use.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P284	[In case of inadequate ventilation] wear respiratory protection.
P273	Avoid release to the environment.

Response:

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice / attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

Storage:

P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
------------------	--

Disposal:

P501	Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
-------------	---

2.2. Other hazards

Information not available

3. Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Isocyanic acid, polymethylenepolyphenylene ester	(CAS-No.) 9016-87-9	20-35	Carcinogenicity, category 2 H351, Acute toxicity, category 4 H332, Specific target organ toxicity - repeated exposure, category 2 H373, Eye irritation, category 2 H319, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335, Respiratory sensitization, category 1 H334, Skin sensitization, category 1 H317
1,4-dichlorobenzene	(CAS-No.) 106-46-7	0.5-5	Carcinogenicity, category 2 H351, Eye irritation, category 2 H319, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment, chronic toxicity, category 1 H410 M=1
isobutane	(CAS-No.) 75-28-5	2.5 - 10	Flammable gas, category 1 H220, Pressurised gas H280
propane	(CAS-No.) 74-98-6	2.5 - 10	Flammable gas, category 1 H220, Pressurised gas H280
dimethyl ether	(CAS-No.) 115-10-6	2.5 - 10	Flammable gas, category 1 H220, Pressurised gas H280

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

USA NIOSH-REL
USA OSHA-PEL
USA CAL/OSHA-PEL

NIOSH publication No. 2005-149, 3th printing, 2007.
Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).

Isobutane							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15min		Remarks /	
		mg/m3	ppm	mg/m3	ppm	Observations	
NIOSH	USA	1900	800				

1,4-dichlorobenzene							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15min		Remarks /	
		mg/m3	ppm	mg/m3	ppm	Observations	
OSHA	USA	450	75				
CAL/OSHA	USA	60	10	675	110		

Legend: (C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protective Gloves

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a NIOSH certified combined filter should be worn (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value
Appearance	Liquid under pressure
Colour	yellowish
Odour	not available
Odour threshold	not available
pH	not available
Melting point / freezing point	not available
Initial boiling point	not available
Boiling range	not available
Flash point	not available
Evaporation rate	not available
Flammability	Extremely flammable aerosol
Lower explosive limit	not available
Upper explosive limit	not available
Vapour pressure	5 Bar
Vapour density	not available
Relative density	not available
Solubility	not available
Partition coefficient: n-octanol/water	not available
Auto-ignition temperature	not available
Decomposition temperature	not available
Viscosity	not available
Explosive properties	not available
Oxidising properties	not available

9.2. Other information

Information not available

10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

Information not available

11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Acute toxicity, category 4. Harmful if inhaled.

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Sensitising for the respiratory system

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

Issue date: 09.12.2024 Version: 0.0

CARCINOGENICITY

Suspected of causing cancer

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, and OSHA.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

PROPANE

Solubility in water 0.1 - 100 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

PROPANE

Partition coefficient: n-octanol/water 1.09

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage than 0,1%.

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
p-Dichlorobenzene 106-46-7	U072	Included in waste streams: F039, K149, K150	7.5 mg/L regulatory level	U072
Chemical name	RCRA – Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
p-Dichlorobenzene 106-46-7	Category II- Semi-volatiles			

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: UN 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous



STANLEY®

Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: -- Special provision: 190, 327, 344, 625	Limited Quantities: 1 lt	Tunnel restriction code: (D)
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 lt	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 150 kg Maximum quantity: 75 kg A145, A167, A802	Packaging instructions: 203 Packaging instructions: 203

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

Clean Air Act Section 112(b):

106-46-7	1,4-dichlorobenzene
----------	---------------------

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act Priority Pollutants:

106-46-7	1,4-dichlorobenzene
----------	---------------------

Clean Water Act Toxic Pollutants:

106-46-7	1,4-dichlorobenzene
----------	---------------------

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

EPA List of Lists:

313 Category Code:

9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester
106-46-7	1,4-dichlorobenzene

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

106-46-7	1,4-dichlorobenzene
----------	---------------------

EPCRA 313 TRI:

9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester
106-46-7	1,4-dichlorobenzene

RCRA Code:

106-46-7	1,4-dichlorobenzene
----------	---------------------

CAA 112 (r) RMP TQ:

74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hydrocarbon alkanes, C1-C4))
115-10-6	DME
75-28-5	Isobutane

State Regulations

Massachusetts:

74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hydrocarbon alkanes, C1-C4))
115-10-6	DME
75-28-5	Isobutane
106-46-7	1,4-dichlorobenzene

Minnesota:

74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hydrocarbon alkanes, C1-C4))
115-10-6	DME
106-46-7	1,4-dichlorobenzene

New Jersey:

74-98-6	PROPANE (Alkanes, Alkanes (aliphatic hydrocarbon alkanes, C1-C4))
115-10-6	DME
9016-87-9	Isocyanic acid, polymethylenepolyphenylene ester
75-28-5	Isobutane
106-46-7	1,4-dichlorobenzene



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

New York:

106-46-7 1,4-dichlorobenzene

Pennsylvania:

74-98-6 PROPANE (Alkanes, Alkanes (aliphatic hydrocarbon alkanes, C1-C4))
115-10-6 DME
75-28-5 Isobutane
106-46-7 1,4-dichlorobenzene

California:

106-46-7 1,4-dichlorobenzene

Proposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

106-46-7 1,4-dichlorobenzene

NSRL / MADL (µg/day)					
Hazard type	Oral	Dermal	Inhalation	Intravenous	Note
Carcinogenicity	20				-

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 @ RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112@)
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112@ of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323



Stanley F 993 Foam Sealant Pest Block

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012
Issue date: 09.12.2024 Version: 0.0

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

STANLEY SDS

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.