

## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

NUCLEUS INCORPORATED  
13901 WILLARD RD, CHANTILLY, VA 20151  
+1 703 988 7773

#### 1.4. Emergency telephone number

For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident  
Call CHEMTREC Day or Night  
1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

|   |      |
|---|------|
| Flammable aerosol Category 1                                  | H222 |
| Acute toxicity (inhalation:gas) Category 4                    | H332 |
| Skin corrosion/irritation Category 2                          | H315 |
| Serious eye damage/eye irritation Category 2A                 | H319 |
| Respiratory sensitisation Category 1                          | H334 |
| Skin sensitization Category 1                                 | H317 |
| Carcinogenicity Category 2                                    | H351 |
| Specific target organ toxicity (single exposure) Category 3   | H335 |
| Specific target organ toxicity (repeated exposure) Category 2 | H373 |

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H222 - Extremely flammable aerosol  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H335 - May cause respiratory irritation  
H351 - Suspected of causing cancer  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, sparks, open flames. - No smoking  
P211 - Do not spray on an open flame or other ignition source

## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0

P251 - Pressurized container: Do not pierce or burn, even after use  
 P261 - Avoid breathing gas, spray, vapors  
 P280 - Wear eye protection, face protection, protective clothing, protective gloves  
 P284 - [In case of inadequate ventilation] wear respiratory protection  
 P302+P352 - If on skin: Wash with plenty of water  
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P308+P313 - If exposed or concerned: Get medical advice/attention  
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name   | Product identifier  | %        | GHS-US classification   |
|--|---------------------|----------|---|
| Isocyanic acid, polymethylenepolyphenylene ester | (CAS No) 9016-87-9  | 20 - 35  | Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Resp. Sens. 1, H334<br>Skin Sens. 1, H317<br>Carc. 2, H351<br>STOT SE 3, H335<br>STOT RE 2, H373 |
| 2-Propanol, 1-chloro-, phosphate (3:1)           | (CAS No) 13674-84-5 | 10 - 30  | Acute Tox. 4 (Oral), H302   |
| isobutane  | (CAS No) 75-28-5    | 2.5 – 15 | Flam. Gas 1, H220   |
| propane  | (CAS No) 74-98-6    | 2.5 – 15 | Flam. Gas 1, H220   |
| dimethyl ether                                   | (CAS No) 115-10-6   | 2.5 – 15 | Flam. Gas 1, H220   |

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Eye irritation.

## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurized container: may burst if heated.  
Reactivity : Extremely flammable aerosol. Pressurized container: may burst if heated.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0

| THERMAL&SOUND INSULATION SPRAY FOAM                                 |                                  |
|---|----------------------------------|
| <b>USA - ACGIH - Occupational Exposure Limits</b>                   |                                  |
| Local name  | Propane                          |
| ACGIH STEL (ppm)  | 1000 ppm (EX - Explosion hazard) |
| Remark (ACGIH)  | TLV® Basis: Simple Asphyxiant    |
| Regulatory reference  | ACGIH 2020                       |
| <b>USA - OSHA - Occupational Exposure Limits</b>                    |                                  |
| Local name  | Propane                          |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                                 | 1800 mg/m <sup>3</sup>           |
| OSHA PEL (TWA) (ppm)  | 1000 ppm                         |
| Regulatory reference (US-OSHA)                                      | OSHA Annotated Table Z-1         |
| <b>Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)</b> |                                  |
| No additional information available                                 |                                  |
| <b>isobutane (75-28-5)</b>  |                                  |
| <b>USA - ACGIH - Occupational Exposure Limits</b>                   |                                  |
| Local name  | Isobutane                        |
| ACGIH STEL (ppm)  | 1000 ppm (EX - Explosion hazard) |
| Remark (ACGIH)  | TLV® Basis: CNS impair           |
| Regulatory reference  | ACGIH 2020                       |
| <b>propane (74-98-6)</b>  |                                  |
| <b>USA - ACGIH - Occupational Exposure Limits</b>                   |                                  |
| Local name  | Propane                          |
| Remark (ACGIH)  | TLV® Basis: Simple Asphyxiant    |
| Regulatory reference  | ACGIH 2020                       |
| <b>USA - OSHA - Occupational Exposure Limits</b>                    |                                  |
| Local name  | Propane                          |
| OSHA PEL (TWA) (mg/m <sup>3</sup> )                                 | 1800 mg/m <sup>3</sup>           |
| OSHA PEL (TWA) (ppm)  | 1000 ppm                         |
| Regulatory reference (US-OSHA)                                      | OSHA Annotated Table Z-1         |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
 Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves. EN 374. Nitrile rubber gloves

#### Eye protection:

Chemical goggles or safety glasses. EN 166.

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. EN 14387

**Personal protective equipment symbol(s):**

## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0



### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|   |   |
|---|---|
| Physical state                              | : Gas   |
| Appearance                                  | : Liquid under pressure.                      |
| Color                                       | : Blue  |
| Odor  | : Characteristic                              |
| Odor threshold                              | : No data available                           |
| pH  | : No data available                           |
| Melting point                               | : No data available                           |
| Freezing point                              | : No data available                           |
| Boiling point                               | : No data available                           |
| Flash point                                 | : No data available                           |
| Relative evaporation rate (butyl acetate=1) | : No data available                           |
| Flammability (solid, gas)                   | : No data available                           |
| Explosion limits                            | : No data available                           |
| Explosive properties                        | : Pressurized container: may burst if heated. |
| Oxidizing properties                        | : No data available                           |
| Vapor pressure                              | : 5 bar                                       |
| Relative density                            | : No data available                           |
| Relative vapor density at 20 °C             | : No data available                           |
| Specific gravity / density                  | : 17 - 28 kg/m <sup>3</sup>                   |
| Solubility                                  | : No data available                           |
| Log Pow                                     | : No data available                           |
| Auto-ignition temperature                   | : No data available                           |
| Decomposition temperature                   | : No data available                           |
| Viscosity                                   | : No data available                           |
| Viscosity, kinematic                        | : No data available                           |
| Viscosity, dynamic                          | : No data available                           |

#### 9.2. Other information

|             |           |
|-------------|-----------|
| VOC content | : < 2 g/l |
|-------------|-----------|

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Harmful if inhaled.

| 2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5) |   |
|---|---|
| LD50 dermal rabbit                                  | > 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| ATE US (oral)                                       | 500 mg/kg bodyweight  |

| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) |              |
|--|--------------|
| ATE US (gases)   | 4500 ppmv/4h |
| ATE US (vapours)   | 11 mg/l/4h   |
| ATE US (dust,mist)   | 1.5 mg/l/4h  |

Skin corrosion/irritation : Causes skin irritation.  
 Serious eye damage/irritation : Causes serious eye irritation.  
 Respiratory or skin sensitization : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Suspected of causing cancer.

| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) |                      |
|--|----------------------|
| IARC group   | 3 - Not classifiable |

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) |                                   |
|--|-----------------------------------|
| STOT-single exposure   | May cause respiratory irritation. |

Reproductive toxicity : Not classified

| 2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5) |   |
|---|---|
| LOAEL (animal/female, F0/P)                         | 99 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |
| NOAEL (animal/male, F0/P)                           | 85 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)   |

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) |  |
|--|--|
| STOT-repeated exposure                                       | May cause damage to organs through prolonged or repeated exposure. |

Aspiration hazard : Not classified  
 Symptoms/injuries after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.  
 Symptoms/injuries after eye contact : Eye irritation.

## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

| 2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5) |   |
|---|---|
| LC50 fish 1   | 51 mg/l Test organisms (species): Pimephales promelas                 |
| EC50 Daphnia 1                                      | 131 mg/l Test organisms (species): Daphnia magna                      |
| NOEC (chronic)                                      | 32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'      |
| NOEC chronic fish                                   | 5.2 mg/l Test organisms (species): other:Fish – chronic QSAR (Esters) |

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0

Emergency Response Guide (ERG) Number : 126  
 Other information : No supplementary information available.

### TDG

No additional information available

### Transport by sea

UN-No. (IMDG) : 1950  
 Proper Shipping Name (IMDG) : AEROSOLS  
 Class (IMDG) : 2 - Gases  
 MFAG-No : 126

### Air transport

UN-No. (IATA) : 1950  
 Proper Shipping Name (IATA) : Aerosols, flammable  
 Class (IATA) : 2

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
 Subject to reporting requirements of United States SARA Section 313

|                          |   |
|--------------------------|---|
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711). |
|--------------------------|---|

#### isobutane (75-28-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
 Not subject to reporting requirements of the United States SARA Section 313

#### propane (74-98-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
 Not subject to reporting requirements of the United States SARA Section 313

### 15.2. International regulations

#### CANADA

#### Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

Listed on the Canadian DSL (Domestic Substances List)

#### isobutane (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

#### propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

No additional information available

### 15.3. US State regulations

| Component   | State or local regulations   |
|---|--|
| Isocyanic acid, polymethylenepolyphenylene ester(9016-87-9) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List |



## STANLEY THERMAL&SOUND INSULATION SPRAY FOAM

Issue date: 17.07.2023 Version: 0.0

| Component          | State or local regulations  |
|--------------------|---|
| isobutane(75-28-5) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. – New York City – Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |
| propane(74-98-6)   | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. – New York City – Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |

### SECTION 16: Other information

Full text of H-statements:

|      |  |
|------|--|
| H220 | Extremely flammable gas.   |
| H280 | Contains gas under pressure; may explode if heated.                        |
| H315 | Causes skin irritation.  |
| H317 | May cause an allergic skin reaction.                                       |
| H319 | Causes serious eye irritation.   |
| H332 | Harmful if inhaled.  |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation.  |
| H351 | Suspected of causing cancer.   |
| H373 | May cause damage to organs through prolonged or repeated exposure.         |

SDS US STANLEY

*DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable*