

STANLEY® A 550 ULTIMATE GRAB INSTANT ADHESIVE KIT™



DESCRIPTION

STANLEY A 550 ULTIMATE GRAB INSTANT ADHESIVE KIT is a high-performance adhesive solution, ideal for both professional and DIY applications. The kit includes a high-viscosity cyanoacrylate adhesive and a specialized activator that works together to ensure fast, strong bonding across a wide range of materials. The activator prevents the adhesive from being absorbed by porous surfaces, increasing bond strength and ensuring a more durable hold. With its high viscosity, the adhesive is perfect for use on vertical surfaces, as it won't drip or slump, allowing for precise and controlled application. The fast-curing formula, enhanced by the activator, is particularly beneficial for applications where rapid bonding is required. Suitable for a variety of materials, including plastics, metals, wood, and ceramics. STANLEY® A 550 Kit is a reliable and efficient solution for quick, long-lasting repairs or projects that demand both speed and strength.

PRODUCT FEATURES

- **Rapid bonding:** Provides an extremely fast bonding experience.
- **Strong bonding power:** Offers high adhesive strength for reliable bonds.
- **Vertical application:** Suitable for use on vertical surfaces without dripping or slumping.
- **Enhanced bonding on difficult substrates:** Particularly effective for bonding porous or uneven surfaces by preventing absorption of the adhesive, resulting in increased bonding strength.

APPLICATIONS

- This adhesive is suitable for bonding a wide range of materials, including acidic and porous surfaces.
- Fast bonding times make it ideal for time-sensitive applications.
- It is compatible with substrates such as MDF, wood, chip wood, rubber, most plastics, leather, and other common materials.
- Especially suitable for applications requiring accelerated cure speed.
- Offers some gap-filling ability, enhancing versatility in various applications.
- Recommended for use on close-fitting parts and smooth surfaces.

PRODUCT INFORMATION

PACKAGING	3.4 Fl.Oz. / 100 ml + 0.88 Fl.Oz. / 25 gr
	16.9 Fl.Oz. / 500 ml + 3.4 Fl.Oz. / 100 gr
	12 pcs in box
SHELF LIFE	15 Months
STORAGE	At cool and dry ambient. In between +41°F to +95°F. max. 60% relative humidity.
SKU	COLOR
SXAD 2063-01	Colorless



Scan the QR Code to see the full line of Stanley Products

KEY FEATURES

- FAST CURING INSTANT ADHESIVE
- BONDING WIDE RANGE OF MATERIALS
- NO DRIP OR SLUMP


DIRECTIONS FOR USE

- Ensure that the substrates are dry, clean, and free from dust and grease before application.
- At least one substrate should have a smooth surface and a sufficient connection area.
- Apply a drop of adhesive on one substrate.
- Use the spray activator on the other substrate.
- Join the substrates together and press firmly for a few seconds.
- The recommended application temperature is between +41°F and +95°F.

LIMITATIONS

- It is advisable to store cyanoacrylates in their original sealed containers until use.
- Avoid exposing the adhesive to strong light and heat sources.
- Cyanoacrylates can bond to the skin within seconds, so avoid contact. In case of skin or eye contact, seek immediate medical attention.
- Ensure proper closure of the container to prevent the adhesive from hardening.
- The activator is flammable, so do not expose it to fire.
- The activator box is pressurized, do not crush, or drill it.





STANLEY® A 550 ULTIMATE GRAB INSTANT ADHESIVE KIT™

TECHNICAL DATA

GLUE

PARAMETER	TEST METHOD / CONDITIONS	VALUE
BASIS		Ethyl Cyanoacrylate
CONSISTENCY	ISO 7390	Liquid gel
DENSITY	ISO 1183-1	8,96 (lbs per gallon)
FLASHPOINT		> 177°F
VISCOSITY	ASTM D1084	1200 - 1800 Cps at 77°F
TEMPERATURE RESISTANCE	(Ambient and surface)	Between -4°F and +158°F
APPLICATION TEMPERATURE	(Ambient and surface)	Between +41°F and +95°F

ACTIVATOR

PARAMETER	TEST METHOD / CONDITIONS	VALUE
BASIS		Hexane
CONSISTENCY	ISO 7390	Aerosol
TEMPERATURE RESISTANCE	(Ambient and surface)	Colorless
APPLICATION TEMPERATURE	(Ambient and surface)	Between -4°F and +158°F

SAFETY

Ensure good ventilation of the workstation. Wear personal protective equipment. Do not eat, drink, or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety.

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions, or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

01.01.2025 rev.0

BEST TO USE WITH

	SKU NUMBER	PRODUCT NAME