



STANLEY® A 603 ULTIMATE GRAB NO NEED NAILS™



DESCRIPTION

STANLEY A 603 ULTIMATE GRAB NO NEED NAILS is a one-part, high-quality, multi-purpose, initial tack, versatile acrylic adhesive, suitable for assembly of light weight construction materials and structural elements.

STANLEY A 603 is paintable with latex or oil-based paints. It is easy to apply and tool, low in odor and cleans up easily with water.

STANLEY A 603 is suitable for bonding EPS, XPS, Rigid PU Foam, Hard PVC decorative profiles and rosettes. It is also suitable for bonding wood, ceramic tiles, acoustic panels, and ventilation.

PRODUCT FEATURES

- Acrylic dispersion based
- Sustainable, Low VOC, solvent free
- Initial tack and direct grip
- Resistant to weather conditions, no odor, paintable
- Fills the gaps on uneven surfaces

APPLICATIONS

- Bonding of MDF, particleboard, fiber plates wood, concrete, brick, natural stone, plaster, ceramic tiles, acoustic panels, faience, plaster, ventilation and PVC cable ducts, and synthetic construction materials
- Installation of moldings, paneling, baseboards, and drywall material
- Suitable for bonding EPS and XPS Ornaments

PRODUCT INFORMATION

PACKAGING	Net 10.1 Fl Oz. / 300 ml plastic cartridges
	12 pcs in box
SHELF LIFE	15 Months
STORAGE	In a cool and dry environment, between +41°F to +77°F.
SKU	COLOR
SXAD 2037-01	White

DIRECTIONS FOR USE

• **SURFACE PREPARATION:** Substrates must be sound quality, clean, dry and free of dust, grease, rust and other contaminants which may affect the adhesion. Non-porous surfaces (such as aluminum, glass, etc.) must be free of any coatings and should be cleaned with a suitable solvent and thoroughly dried with a clean cloth. Porous substrates (such as concrete, brickwork, etc.) must be mechanically cleaned from loose particles or residues with a jet of compressed air, sandpaper or hard brush. Mask off joint edges with self-adhesive tape as protection from contamination.

• **APPLICATION METHOD / TOOLS:** Recommended application and surface temperatures: +41°F and +95°F. Cut nozzle to obtain desired bead size. Apply the adhesive as evenly as possible by using a professional caulking gun. Apply the adhesive on the edges and corners of the materials to be bonded and fix them in the needed position. Before curing surfaces can be repositioned for desired application. Applying pressure can be necessary for fully bonding. During curing, protect the materials from excessive moisture, water and rain

• **CLEANING:** Uncured product may be easily removed with damp sponge. Cured products must be removed mechanically. Hands can be cleaned with warm water and soap.

LIMITATIONS

- Not recommended for sealing joints permanently exposed to water.
- Not recommended to be applied in case of risk of rain or frost.
- Store caulk away from extreme heat or cold.
- Cooler temperatures and higher humidity will slow down dry time.
- The initial pressure is critical to final bonding strength.

SAFETY

Ensure good ventilation of the workstation. Wear personal protective equipment. Do not eat, drink, or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety.



Scan the QR Code to see the full line of Stanley Products

KEY FEATURES

- QUICK REPAIRS ON WALLS
- EXCELLENT ADHESION
- HIGH STRENGTH & DURABILITY



STANLEY® A 603 ULTIMATE GRAB NO NEED NAILS™

TECHNICAL DATA

PARAMETER	TEST METHOD / CONDITIONS	VALUE
BASIS		Acrylic Dispersion
DENSITY	ISO 1183-1	11.7 ± 0,3 (lbs. per gallon)
SKIN FORMATION TIME	Internal (73°F and 50% R.H)	30±10 min
DRYING RATE	Internal (73°F and 50% R.H)	Min. 0,08"/day
MAXIMUM SHEAR STRENGTH	After 6 hours	> 40 kgf/cm ²
	After 24 hours	> 70 kgf/cm ²
TEMPERATURE RESISTANCE	Ambient and surface	Between -14°F and +176°F
APPLICATION TEMPERATURE	Ambient and surface	Between +41°F and +104°F

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions, or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

25.03.2025 rev.1

BEST TO USE WITH

	SKU NUMBER	PRODUCT NAME
	SXAC0422-01	PRO-CG3 Pro Caulking Gun
	SXAC0426-01	Smoothing Tool Set
	SXAC0428-01	Cartridge & Nozzle Cutter