

STANLEY® A 720 ULTIMATE GRAB PREMIUM FAST CURE™



DESCRIPTION

STANLEY A 720 ULTIMATE GRAB PREMIUM FAST CURE is a high-performance, one-component, solvent-free polyurethane adhesive, specifically designed for fast curing and superior initial tack. Its thixotropic (pasty) structure ensures excellent green strength, making it ideal for applications that require quick adhesion. Formulated to bond a wide variety of materials, STANLEY A 720 effectively adheres to wood, metal, stone, concrete, and most plastics. Suitable for both interior and exterior use, it excels in vertical applications and delivers strong adhesion even to damp or moisture-contaminated surfaces.

PRODUCT FEATURES

- High initial tack and green strength.
- Good wet tack.
- Provides excellent green strength.
- Suitable for both indoor and outdoor applications
- Thixotropic, non-sag, ideal for vertical joints
- Low consumption, economical

APPLICATIONS

- Suitable on surfaces such as wood, particleboard, wood, polystyrene foam, concrete, masonry, tile, ceramic, stone, plasterboards.
- Mounting wooden construction elements, wood and plaster panels, plaster ornaments and decorative wooden trimmings.

PRODUCT INFORMATION

PACKAGING	Net 10.1 Fl Oz. / 300 ml plastic cartridges
	12 pcs in box
SHELF LIFE	12 Months
STORAGE	In a cool and dry environment, between +41°F to +77°F.
COLOR	Beige
SKU	SXAD 2039-01

DIRECTIONS FOR USE

- **SURFACE PREPARATION:** Substrates must be sound quality, clean, dry and free of dust, grease, rust and other contaminants which may affect the adhesion. Non-porous surfaces (such as aluminum, glass, etc.) must be free of any coatings and should be cleaned with a suitable solvent and thoroughly dried with a clean cloth. Porous substrates (such as concrete, brickwork, etc.) must be mechanically cleaned from loose particles or residues with a jet of compressed air, sandpaper or hard brush. Mask off joint edges with self-adhesive tape as protection from contamination. Moistening the substrates slightly will provide stronger adhesion.
- **APPLICATION METHOD / TOOLS:** Recommended application and surface temperatures: +41°F and +95°F. Cut nozzle to obtain desired bead size. Apply the sealant as evenly as possible by using a professional caulking gun. Adhesive should be applied to only one side in straight or wave-like form within 2 minutes. Mechanical fasteners must be used to keep the materials together (1-2 hours.) until the adhesive cures totally.
- **CLEANING:** Fresh adhesive can be cleaned with acetone. Cured products must be removed mechanically. Hands can be cleaned with warm water and soap.

LIMITATIONS

- Not suitable for PE, PP, Nylon, ABS, PFTE.
- Not suitable in combination with chlorides
- Not recommended for confined spaces where sealant cannot cure due to lack of atmospheric moisture.
- Protect from water, frost, and adverse air conditions in application.
- Specific substrates not listed in TDS should be tested before application.

SAFETY

Ensure good ventilation of the workstation. Wear personal protective equipment. Do not eat, drink, or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety.



Scan the QR Code to see the full line of Stanley Products

KEY FEATURES

- HIGH INITIAL TACK & HOLD
- GOOD WET TACK
- INDOOR / OUTDOOR APPLICATIONS





STANLEY® A 720 ULTIMATE GRAB PREMIUM FAST CURE™

TECHNICAL DATA

PARAMETER	TEST METHOD / CONDITIONS	VALUE
BASIS		Polyurethane
CURING MECHANISM		Moisture Curing
CONSISTENCY		Thixotropic
TACK-FREE TIME	ASTM C679	15±5 min
SHRINKAGE		None
PRESSING TIME		30 mins*
SPECIFIC GRAVITY	ASTM D792	12 ± 0.03 lb/gal
MAXIMUM SHEAR STRENGTH	After 24 hrs	> 70 kgf/cm ²
TEMPERATURE RESISTANCE	Ambient and surface	Between -4°F and +158°F
APPLICATION TEMPERATURE	Ambient and surface	Between +41°F and +95°F

*Pressing time depends on ambience conditions (temperature, humidity etc.) and porosity of the surfaces to be bonded.

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions, or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

25.03.2025 rev.1

BEST TO USE WITH

	SKU NUMBER	PRODUCT NAME
	SXAC0424-01	PRO-CG1 Pro Caulking Gun
	SXAC0426-01	Smoothing Tool Set
	SXAC0428-01	Cartridge & Nozzle Cutter