



STANLEY® A 772 ULTIMATE GRAB WOOD FLOORING ADHESIVE™

DESCRIPTION

STANLEY A 772 ULTIMATE GRAB WOOD FLOORING ADHESIVE is a high-performance, single-component adhesive formulated with advanced hybrid technology. This innovative formula is free from solvents, isocyanates, and water, making it an environmentally friendly and safe solution for wood flooring installations. The adhesive offers exceptional bonding strength, making it ideal for a variety of wood flooring types, including strips, mosaic parquet, plank floors, and wood block floors. It delivers reliable performance on both porous and non-porous substrates, ensuring a strong and durable bond that withstands the test of time. The elastic nature of the adhesive also allows for flexibility, accommodating the natural movement of the wood and contributing to long-lasting, secure flooring applications.

PRODUCT FEATURES

- Ready to use: No mixing required
- Cost effective
- Non-toxic, eco-friendly
- Form stable peaks when applied by a notched trowel
- Suitable for under-floor heating systems
- High bonding strength
- Solvent, Isocyanate and water free
- Very easy to apply

APPLICATIONS

- Suitable for bonding many different types of floors including strips and mosaic parquet, plank floors and wood block floors on porous and non-porous substrates.

PRODUCT INFORMATION

PACKAGING	2,72 gallon /10,25 Liters
	1 pcs in box
SHELF LIFE	9 Months
STORAGE	Between 41°F to 77°F in unopened package.
SKU	COLOR
SXHF 4011-01	Beige

DIRECTIONS FOR USE

- Before the application, be sure that the surface is dry, clean, smooth and free from dust and irregularities
- Open the pail and cut the aluminium foil bag.
- Do not dilute the adhesive in any manner.
- In order to ensure good processing properties, the minimum temperature of the adhesive should be at least 41°F.
- Apply the adhesive with a dented trowel.
- Working time is around 30 min. at 73.4°F, 50% R.H.
- Be sure that the adhesive is wet the surface evenly.
- The adhesive cures with humidity therefore in order to ensure proper drying, adequate air humidity is necessary.
- Once opened the product inside the foil bag must be used up in a short time.
- Clean the adhesive with a cloth if the adhesive is still wet. Once it has hardened, it can be cleaned mechanically.
- Walking on parquet can be done after 24 hours.
- Follow wood flooring manufacturer's guidelines for special precautions during installation.
- Applied Quantities:
- For strips- and mosaic parquet use 20.38 ft²/gallon
- For plank, and wood block parquet use 40.76 ft²/gallon.
- If the moisture content is above 65% RH always use 40.76 ft²/gallon.

LIMITATIONS

- Do not set flooring on the adhesive if the skin has formed.
- Do not apply on frozen surfaces or standing water.
- Do not use on wet, contaminated or friable substrates.



Scan the QR Code to see the full line of Stanley Products

KEY FEATURES

- XX
- XX
- XX





STANLEY® A 772 ULTIMATE GRAB WOOD FLOORING ADHESIVE™

TECHNICAL DATA

PARAMETER	TEST METHOD / CONDITIONS	VALUE
BASIS		Hybrid Polymer
CURING SYSTEM		Moisture
DENSITY		13.02 ± 0.03 (lbs. per gallon)
APPEARANCE		Homogeneous paste
SKIN FORMATION TIME	Internal (73°F and 50% R.H)	50±10
CURING RATE	Internal (73°F and 50% R.H)	Min. 2,5 mm/day
SAGGING	ISO 7390	None
SHORE A HARDNESS	ISO 868	40-50
ELONGATION AT BREAK %	ISO 37	Min. 150%
VOLUME LOSS	ISO 10563	< 3%
TENSILE STRENGTH	ISO 37	Min. 174.05 psi
TEMPERATURE RESISTANCE	Ambient and surface	Between -4°F and +176°F
APPLICATION TEMPERATURE	Ambient and surface	Between +41°F and +86°F

SAFETY

Ensure good ventilation of the workstation. Wear personal protective equipment. Do not eat, drink, or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety.

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions, or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

01.01.2025 rev.0

BEST TO USE WITH

	SKU NUMBER	PRODUCT NAME