

STANLEY® AP 95 SPECIAL CARE TIRE REPAIR & INFLATOR™



DESCRIPTION

STANLEY AP 95 SPECIAL CARE TIRE REPAIR & INFLATOR is a high-performance, single-component tire repair spray designed for professional applications. It provides a quick and reliable method for repairing and inflating tires without removing them from the rim. The formulation seals punctures from the inside, creating a secure and durable bond without damaging the tire structure. The repair process is fast and efficient, restoring tire pressure and functionality within seconds.

PRODUCT FEATURES

- **No Tools Required:** Enables tire repair without the use of a jack or additional tools, offering a quick and hassle-free solution.
- **Self-Sealing:** Automatically locates and seals punctures within the tire, restoring airtight integrity.
- **Water-Based Formula:** Eco-friendly, water-based formulation allows for easy cleanup after use.
- **Tire Valve Safe:** Compatible with all standard tire valves; will not clog or damage the valve mechanism.
- **Instant Tire Repair:** Delivers immediate puncture sealing and inflation, allowing the vehicle to be driven without wheel removal.
- **Integrated Inflation:** Inflates the tire to approximately 14.5-29 psi (1-2 bar), enabling safe continuation of driving at moderate speeds.
- **Safe for Tires and Wheels:** Formulated to be non-corrosive and non-damaging to tire rubber or wheel materials.

PRODUCT INFORMATION

PACKAGING	Net 10.5 Oz. / 210 gr / 300 ml
	12 pcs in box
SHELF LIFE	24 Month
STORAGE	In a cool and dry environment, between +41°F to +86°F. max. 60% relative humidity.
SKU	SXAE0824-01

APPLICATIONS

- **Universal Application:** Suitable for use on a wide range of vehicles, including cars, motorcycles, caravans, and trailers.
- **For Tubeless Tires:** Specifically formulated for the repair of tubeless tires, ensuring optimal compatibility and performance.

DIRECTIONS FOR USE

- **SHAKE THE CAN:** Shake the aerosol can vigorously before use to ensure the contents are well mixed and deliver optimal performance.
- **IDEAL OPERATING TEMPERATURE:** For best results, use the product in ambient temperatures between 41°F and 86°F (5°C to 30°C).
- **POSITION THE VALVE:** Rotate the wheel so that the tire valve is positioned at the bottom (6 o'clock position).
- **DEFLATE THE TIRE:** Fully deflate the tire to prepare it for the repair process.
- **ATTACH THE CAN:** Securely connect the spray can nozzle to the tire valve by screwing it on tightly.
- **APPLY THE PRODUCT:** Invert the can (hold it upside down) and discharge the entire contents into the tire.
- **DRIVE AFTER APPLICATION:** After use, drive immediately for approximately 25-31 miles (40-50 km) at a moderate speed of around 25 mph (40 km/h) to distribute the sealant evenly inside the tire.
- **INFLATE OR REPAIR:** As soon as possible, inflate the tire to the recommended pressure at a service station or have it professionally repaired.
- **INFORM THE TIRE SERVICE:** When visiting a tire service center, inform the technician that STANLEY® AP 95 Special Care Tire Repair & Inflator has been used to ensure proper and safe handling during the repair process.

LIMITATIONS

- **Keep Packaging Sealed:** Always keep the container tightly closed when not in use.
- **Not for Personal Use:** Do not use the product for cleaning hands, skin, face, or any food-related items.
- **Eye Contact:** Avoid contact with eyes. In case of contact, rinse immediately with plenty of water and seek medical attention.
- **Skin Contact:** If the product comes into contact with skin, wash thoroughly with soap and water.
- **Storage Conditions:** Store in a cool, dry, and well-ventilated area between 41°F and 86°F (5°C and 30°C).



Scan the QR Code to see the full line of Stanley Products

KEY FEATURES

- FOR CARS, MOTORCYCLES, CARAVANS AND TRAILERS
- NO NEED FOR JACK
- FOR TUBELESS TIRES OR TIRES WITH INNER TUBES





STANLEY® AP 95 SPECIAL CARE TIRE REPAIR & INFLATOR™

Avoid extreme temperatures, as they may affect product performance.

- Fire Safety: DO NOT BURN. Do not expose to temperatures exceeding 122°F (50°C).
- Keep away from open flames, sparks, or sources of ignition. Do not smoke while using.
- Precaution Near Heat or Flame: Do not spray near open flames, hot surfaces, or incandescent materials.
- Handling and Disposal: Do not pierce, puncture, or incinerate the can, even when empty. Dispose of according to local regulations.
- Test Before Use: Perform a small-scale test application to confirm compatibility before full use.
- Keep Out of Reach of Children: Store securely and away from children at all times.
- Read Instructions: Read and follow all directions carefully before use to ensure safe and proper handling.

TECHNICAL DATA

PARAMETER	VALUE
FORM	AEROSOL
APPEARANCE	White Foam Aerosol
BASE	Water based
SPECIFIC GRAVITY	63.05 ± 0.63 lb/ft ³ (1.01 ± 0.01 g/cm ³)
ODOR	Characteristic
FLASH POINT	N/A

SAFETY

Contains Diphenylmethane-4,4'-Diisocyanate. Harmful if inhaled. Irritating to the eyes, respiratory system, and skin. Avoid breathing the spray/vapor. Wear suitable protective clothing and gloves. Use only in well-ventilated areas. Pressurized container. Keep away from direct sunlight and do not expose to temperatures over 122°F. Do not puncture or burn, even after use. Keep away from sources of ignition and do not smoke. Keep out of the reach of children.

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions, or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

12.11.2025 rev.2